

ALPHA PS1

POWERED SPEAKERS FOR ALL YOUR MEDIA

psb
SPEAKERS



SPECIFICATIONS

FREQUENCY RANGE

On Axis @ 0° ± 3dB	80-22kHz
On Axis @ 0° ± 1 1/2dB	90-20kHz
Off Axis @ 30° ± 3dB	90-12kHz
LF Cutoff -10dB	58Hz

AMPLIFIER POWER

Continuous	20W
Dynamic Peak	40W
Type	Class D

ACOUSTIC DESIGN

Tweeter	3/4" (19mm) Aluminium Dome
Woofers	3 1/2" (90mm) Polypropylene Cone Rubber Surround
Crossover	2100Hz LR4
Internal Volume	.067 ft ³ (1.9 litre)
Design Type	Bass Reflex Rear Slot Port

SIZE (W x H x D)

Gross Dimensions including Feet and Terminals	4 1/2 x 7 7/8 x 6 7/8" (114 x 197 x 174mm)
---	---

WEIGHT

Net	8.3lb (3.8kg)/pr
Shipping	12lb (5.5kg)/pr

FINISH

Gloss Black

FEATURES

Volume Control
Mono Subwoofer Output
Low Level RCA Input
Low Level 1/8" (3mm) "AUX" Input

ACCESSORIES

Power Supply Brick
Power Link
White Drawstring Bag

All specifications are subject to change without notice. PSB, PSB Speakers, and Imagine are trademarks of, or used under license by, PSB Speakers, a division of Lenbrook Industries Limited.
© November 2012 PSB Speakers 12-026. All rights reserved.

REAL SOUND for REAL PEOPLE